



MILITARY &
SECURITY
EXPERTS

The highest quality, best value K12 bollard made.

39 FB K12

K12 Fixed Bollard

DOS Certified K12/L3

Specification

Barrier Construction Details

Description: Barrier is a shallow mounted steel assembly, finished to the specification of the end user. Can span any distance in any color.

Our fixed-in-place, stationary bollard is proven to sustain K12/L3 test impact. This means that the stationary bollard will stop a 15,000 lb Truck moving at 50 mph and the truck will not penetrate more than 3 ft. past the bollard. This is the highest attainable rating.

- Required depth for install is only 18 inches, making it practical where utilities are also buried
- Cost-effective. Five posts on 4-ft. centers make spanning long distances economical.
- Requires standard 3000 psi concrete
- Very easy to install completely onsite in a few hours
- Can be completely functional in a few days
- Available in any finish color.

The bollard assembly is shipped from the factory flat packed with minimal assembly required for install.

Our K12 crash test proved that a hit to a *single post* prevents a 15,000 vehicle traveling 50 mph from penetrating, whereas the only other K12/L3 bollard passed with a hit to *two posts simultaneously*.

Dimensions:

Bollard: 5 posts on 4 ft centers. 16' 10" end to end.

Bollard Height: 39"

Posts: 10" x 10"

Materials: All Structural parts made of structural Steel.



Available in any finish color.



Before



After

To see crash test video visit:

www.offthewallproducts.com

Please call for more information: 801.363.7740

CAGE 1DAL6 GS07F-5736R GS07F-0175J

DUNS 96-0770-147